



45/50/55/60/65/70 SERIES
H/V/W
UTQG-420/A/A

PASSENGER CAR AND MINIVAN

AP028



80/82 SERIES
S/T, M+S
UTQG-320/A/A

PASSENGER CAR AND MINIVAN

S-1010

Tire Size	Tread Depth		Load Index	Speed symbol	Std.Rim	Section Width		Overall Diameter		Load Capacity		Std.Cold Infl.press		Max.permiss.press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
215/70R15	9.0	11.5	98	H	61/2J	221	8.7	683	26.9	750	1653	250	36	300	44
195/65R15	7.9	10.0	91	V	6J	201	7.9	635	25.0	615	1356	250	36	300	44
205/65R15	8.2	10.5	94	V	6J	209	8.2	647	25.5	670	1477	250	36	300	44
215/65R16	8.0	10.0	98	H	61/2J	221	8.7	686	27.0	750	1653	250	36	300	44
195/60R15	8.2	10.5	88	V	6J	201	7.9	615	24.2	560	1235	250	36	300	44
205/60R15	8.4	10.5	91	V	6J	209	8.2	627	24.7	615	1356	250	36	300	44
205/60R16	8.0	10.0	92	V	6J	209	8.2	652	25.7	630	1389	250	36	300	44
215/60R16	8.2	10.5	95	V	61/2J	221	8.7	664	26.1	690	1521	250	36	300	44
225/60R16	8.3	10.5	98	H	61/2J	228	9.0	676	26.6	750	1653	250	36	300	44
	8.3	10.5	98	V	61/2J	228	9.0	676	26.6	750	1653	250	36	300	44
195/55R15	8.2	10.5	85	V	6J	201	7.9	595	23.4	515	1135	250	36	300	44
205/55ZR16	8.2	10.5	91	W	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
215/55ZR17	8.0	10.0	98/XL	W	7J	226	8.9	668	26.3	750	1653	290	42	340	49
225/55ZR16	8.0	10.0	95	W	7J	233	9.2	654	25.7	690	1521	250	36	300	44
225/55ZR17	8.0	10.0	101/XL	W	7J	233	9.2	680	26.8	825	1819	290	42	340	49
225/50ZR17	8.0	10.0	98/XL	W	7J	233	9.2	658	25.9	750	1653	290	42	340	49
	8.0	10.0	91/XL	W	7J	213	8.4	626	24.6	615	1356	290	42	340	49

- Muffler-like trumpet and open horizontal grooves, effectively reduce air compression; Irregular variable pitch tread blocks, minimize the noise and provide a quiet driving experience.
- Middle rib coupled with full tread pattern guarantee perfect rigidity and excellent handling.
- Four vertical drainage ditches ensure excellent drainage and wetlands grip.
- Small grooves on tire shoulder with separated groove on tread pattern blocks provide good grip on wet and dry land.

Tire Size	Tread Depth		Load Index	Speed symbol	Std.Rim	Section Width		Overall Diameter		Load Capacity		Std.Cold Infl.press		Max.permiss.press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
165R13	8.1	10.0	83	T	41/2J	165	6.5	594	23.4	487	1074	240	35	300	44
185R14	8.7	11.0	91	T	5J	184	7.2	652	25.7	615	1356	240	35	300	44
	8.7	11.0	95/XL	S	51/2J	195	7.7	650	25.6	690	1521	290	42	340	49
* 145/80R12	7.1	9.0	74	T	4.00B	145	5.7	537	21.1	375	827	240	35	300	44
* 155/80R12	7.8	10.0	77	T	4.50B	157	6.2	553	21.8	412	908	220	32	300	44
* 155/80R13	7.8	10.0	79	T	41/2J	157	6.2	578	22.8	437	963	240	35	300	44
165/80R13	8.1	10.0	83	T	41/2J	165	6.5	594	23.4	487	1074	240	35	300	44
* 175/80R14	8.4	10.5	88	T	5J	177	7.0	636	25.0	560	1235	230	33	300	44
185/80R14	8.7	11.0	91	T	5J	184	7.2	652	25.7	615	1356	240	35	300	44
	8.7	11.0	95/XL	S	51/2J	195	7.7	650	25.6	690	1521	290	42	340	49

★ 2009 NEW PRODUCT

- 80 series of S and T speed rated OEM tire pattern.
- Tread compound of high level wear resistance.
- Improved comfort through minimized noise levels.
- All-season pattern, super wear resistant and general purpose.



65/70/75/80 SERIES
S/T/H, M+S
UTQG-420/A/A

PASSENGER CAR AND MINIVAN

S-1015



50/55/60/65/70 SERIES
T/H/V
UTQG-420/A/A

PASSENGER CAR AND MINIVAN

S-1023

Tire Size	Tread Depth		Load Index	Speed symbol	Std. Rim	Section Width		Overall Diameter		Load Capacity		Std. Cold Infl. press		Max. perm. press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
155/80R13	7.8	10.0	79	T	41/2J	157	6.2	578	22.8	437	963	240	35	300	44
175/80R14	8.7	11.0	88	T	5J	177	7.0	636	25.0	560	1235	240	35	300	44
185/80R14	8.7	11.0	91	T	5J	184	7.2	652	25.7	615	1356	240	35	300	44
215/70R15	8.7	11.0	95/XL	S	5J	184	7.2	652	25.7	690	1521	290	42	340	49
215/75R15	8.7	11.0	100	T	6J	216	8.5	703	27.7	800	1764	250	36	300	44
★ 145/70R13	7.5	9.5	71	T	41/2J	150	5.9	534	21.0	345	761	250	36	300	44
155/70R13	7.5	9.5	75	T	41/2J	157	6.2	548	21.6	387	853	250	36	300	44
165/70R13	8.0	10.0	79	T	5J	170	6.7	562	22.1	437	960	250	36	300	44
165/70R13	8.0	10.0	83/XL	T	5J	170	6.7	562	22.1	487	1074	290	42	340	49
165/70R14	8.0	10.0	81	T	5J	170	6.7	588	23.1	462	1019	250	36	300	44
165/70R14	8.0	10.0	85/XL	T	5J	170	6.7	588	23.1	515	1135	290	42	340	49
175/70R13	8.5	10.5	82	T	5J	177	7.0	576	22.7	475	1045	250	36	300	44
175/70R14	8.2	10.5	84	T	5J	177	7.0	602	23.7	500	1102	250	36	300	44
175/70R14	8.2	10.5	88/XL	T	5J	177	7.0	602	23.7	560	1235	290	42	340	49
185/70R13	8.2	10.5	86	T	51/2J	189	7.4	590	23.2	530	1168	250	36	300	44
185/70R14	8.3	10.5	88	T	51/2J	189	7.4	616	24.3	560	1235	250	36	300	44
195/70R14	8.5	10.5	91	T	6J	201	7.9	630	24.8	615	1356	250	36	300	44
205/70R14	8.3	10.5	98/XL	T	6J	209	8.2	644	25.4	750	1653	290	42	340	49
155/65R13	8.1	10.0	73	T	41/2J	157	6.2	532	20.9	365	805	250	36	300	44
165/65R13	8.5	10.5	77	T	5J	170	6.7	544	21.4	412	908	250	36	300	44
165/65R14	8.1	10.0	83/XL	T	5J	170	6.7	570	22.4	487	1074	290	42	340	49
175/65R14	8.0	10.0	82	H	5J	177	7.0	584	23.0	475	1047	250	36	300	44
175/65R14	8.0	10.0	82	T	5J	177	7.0	584	23.0	475	1047	250	36	300	44
175/65R14	8.0	10.0	86/XL	T	5J	177	7.0	584	23.0	530	1168	290	42	340	49

★ 2009 NEW PRODUCT

- Optimized tread pattern block make contact area uniform and improved wear resistance, such design has improved the tire operational performance.
- Tread wear-resisting compound makes tire Longer life.
- Four longitudinal straight grooves provide maximum water evacuation and preferable anti-wet and skid capability.
- Big outer-shoulder blocks and tiny inner-shoulder sipes provide great dry and mud grip. Give you more security sense.

Tire Size	Tread Depth		Load Index	Speed symbol	Std. Rim	Section Width		Overall Diameter		Load Capacity		Std. Cold Infl. press		Max. perm. press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
205/70R15	8.3	10.5	96	T	6J	209	8.2	669	26.3	710	1565	250	36	300	44
205/70R15	★ 8.3	10.5	96	H	6J	209	8.2	669	26.3	710	1565	250	36	300	44
215/70R15	9.0	11.5	98	T	61/2J	221	8.7	683	26.9	750	1653	250	36	300	44
★ 185/65R14	8.0	10.0	86	H	51/2J	189	7.4	596	23.5	530	1168	250	36	300	44
185/65R14	8.0	10.0	86	T	51/2J	189	7.4	596	23.5	530	1168	250	36	300	44
195/65R15	8.2	10.5	91	H	6J	201	7.9	635	25	615	1356	250	36	300	44
195/65R15	8.2	10.5	95/XL	T	6J	201	7.9	635	25.0	690	1521	290	42	340	49
205/65R15	★ 8.5	10.5	94	V	6J	209	8.2	647	25.5	670	1477	250	36	300	44
205/65R15	8.5	10.5	94	H	6J	209	8.2	647	25.5	670	1477	250	36	300	44
205/65R15	★ 8.5	10.5	99/XL	H	6J	209	8.2	647	25.5	775	1709	290	42	340	49
215/65R15	7.8	10.0	100/XL	H	61/2J	221	8.7	661	26.0	800	1764	290	42	340	49
215/65R15	7.9	10.0	98	H	61/2J	221	8.7	686	27.0	750	1653	250	36	300	44
215/65R16	7.9	10.0	102/XL	H	61/2J	221	8.7	686	27.0	850	1874	290	42	340	49
185/60R14	8.0	10.0	82	H	51/2J	189	7.4	578	22.8	475	1047	250	36	300	44
★ 185/60R15	8.0	10.0	84	H	51/2J	189	7.4	603	23.7	500	1102	250	36	300	44
185/60R15	8.0	10.0	88/XL	H	51/2J	189	7.4	603	23.7	560	1235	290	42	340	49
★ 195/60R14	★ 8.3	10.5	86	H	6J	201	7.9	590	23.2	530	1168	250	36	300	44
195/60R14	8.3	10.5	88	H	6J	201	7.9	615	24.2	560	1235	250	36	300	44
195/60R15	★ 8.3	10.5	88	V	6J	201	7.9	615	24.2	560	1235	250	36	300	44
205/60R15	8.3	10.5	91	H	6J	209	8.2	627	24.7	615	1356	250	36	300	44
205/60R16	8.0	10.0	92	H	6J	209	8.2	630	25.2	630	1389	250	36	300	44
205/60R16	★ 8.0	10.0	92	V	6J	209	8.2	652	25.7	630	1389	250	36	300	44
215/60R15	8.0	10.0	94	H	61/2J	221	8.7	639	25.2	670	1477	250	36	300	44
215/60R16	7.8	10.0	95	H	61/2J	221	8.7	664	26.1	690	1521	250	36	300	44
225/60R15	8.2	10.5	96	V	61/2J	228	9.0	651	25.6	710	1565	250	36	300	44
225/60R16	8.3	10.5	98	H	61/2J	228	9.0	676	26.6	750	1653	250	36	300	44
195/55R15	8.2	10.5	85	H	6J	201	7.9	595	23.4	515	1135	250	36	300	44
195/55R15	8.2	10.5	85	V	6J	201	7.9	595	23.4	515	1135	250	36	300	44
195/55R16	7.9	10.0	87	V	6J	201	7.9	620	24.4	545	1201	250	36	300	44
195/55R16	7.9	10.0	91/XL	H	6J	201	7.9	620	24.4	615	1356	290	42	340	49
★ 205/55R16	8.3	10.5	91	H	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
205/55R16	8.3	10.5	91	V	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
195/55R15	8.0	10.0	82	H	6J	201	7.9	577	22.7	475	1047	250	36	300	44

★ 2009 NEW PRODUCT

- Pattern design for deluxe and comfortable sports cars. Bi-bias arc-shaped pattern makes for low rolling resistance and strong shock absorption.
- Superb performance on wet road. Six continuous straight grooves make for highly efficient water dispersal and minimize the possibility of skidding on wet and slippery road.
- Outstanding performance also benefits from wide and flat tread.
- Extremely low road noise gives you a comfortable riding on road surface.
- Luxurious design shows superiority of quality to the best.
- Unique outside appearance without peers.



55 SERIES
V
UTQG-420/A/A

RUN-FLAT TIRE

S-1023



35/40/45/50/55/60/65 SERIES
H/V/W, M+S
UTQG-280/A/A

HUP

S-1063

Tire Size	Tread Depth		Load Index	Speed symbol	Std.Rim	Section Width		Overall Diameter		Load Capacity		Std.Cold Inf.press		Max.permiss.press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
* 195/55RF16	7.9	10.0	87	V	6J	201	7.9	620	24.4	545	1201	250	36	300	44

★ 2009 NEW PRODUCT

- With RFT you remain mobile in the event of a flat tire. You can reach your destination or tire service facility without the bother of having to replace a flat tire with the spare tire.
- Compatible with standard rims.
- Simple mounting.



45/55 SERIES
V

RUN-FLAT TIRE

S-1063

Tire Size	Tread Depth		Load Index	Speed symbol	Std.Rim	Section Width		Overall Diameter		Load Capacity		Std.Cold Inf.press		Max.permiss.p res	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
195/55RF16	7.9	10.0	87	V	6J	201	7.9	620	24.4	545	1201	250	36	300	44
	8.0	10.0	87	V	6J	201	7.9	620	24.4	545	1201	250	36	300	44
* 205/45RF17	8.0	10.0	84	V	7J	206	8.1	616	24.3	500	1102	250	36	300	44
	8.0	10.0	88/XL	V	7J	206	8.1	616	24.3	560	1235	390	42	340	49

★ 2009 NEW PRODUCT

- With RFT you remain mobile in the event of a flat tire. You can reach your destination or tire service facility without the bother of having to replace a flat tire with the spare tire.
- Compatible with standard rims.
- Simple mounting.

Tire Size	Tread Depth		Load Index	Speed symbol	Std.Rim	Section Width		Overall Diameter		Load Capacity		Std.Cold Inf.press		Max.permiss.press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
195/65R15	7.9	10.0	91	V	6J	201	7.9	635	25.0	615	1356	250	36	300	44
* 205/60R16	8	10.0	92	V	6J	209	8.2	652	25.7	630	1389	250	36	300	44
195/55R16	8.0	10.0	87	V	6J	201	7.9	620	24.4	545	1201	250	36	300	44
205/55R16	8.2	10.5	91	V	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
	8.2	10.5	91	H	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
205/55ZR16	8.2	10.5	91	V	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
205/55R16	8.2	10.5	91	V	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
215/55R16	8.0	10.0	93	V	7J	226	8.9	642	25.3	650	1433	250	36	300	44
215/55ZR16	8.0	10.0	93	W	7J	226	8.9	642	25.3	650	1433	250	36	300	44
	8.0	10.0	97/XL	W	7J	226	8.9	642	25.3	730	1609	290	42	340	49
215/55ZR17	7.9	10.0	98/XL	W	7J	226	8.9	668	26.3	750	1653	290	42	340	49
	7.9	10.0	94	W	7J	226	8.9	668	26.3	670	1477	250	36	300	44
225/55R16	8.0	10.0	95	V	7J	233	9.2	654	25.7	690	1521	250	36	300	44
	* 8.0	10.0	99/XL	V	7J	233	9.2	654	25.7	775	1709	290	42	340	49
225/55ZR16	8.0	10.0	95	W	7J	233	9.2	654	25.7	690	1521	250	36	300	44
* 225/55ZR17	8.0	10.0	101/XL	W	7J	233	9.2	680	26.8	825	1819	290	42	340	49
205/50R15	8.0	10.0	86	V	61/2J	214	8.4	587	23.1	530	1168	250	36	300	44
* 215/50ZR17	8.0	10.0	91	W	7J	226	8.9	648	25.5	615	1356	250	36	300	44
	8.0	10.0	95/XL	W	7J	226	8.9	648	25.5	690	1521	290	42	340	49
225/50R16	8.1	10.0	92	V	7J	233	9.2	632	24.9	630	1389	250	36	300	44
225/50ZR16	8.1	10.0	96/XL	W	7J	233	9.2	632	24.9	710	1565	290	42	340	49
	8.1	10.0	92	W	7J	233	9.2	632	24.9	630	1389	250	36	300	44
225/50ZR17	8.0	10.0	98/XL	W	7J	233	9.2	658	25.9	750	1653	290	42	340	49
225/50ZR17	8.0	10.0	94	W	7J	233	9.2	658	25.9	670	1477	250	36	300	44
195/45R15	7.9	10.0	78	V	61/2J	195	7.7	557	21.9	425	937	250	36	300	44
195/45R16	8.0	10.0	84/XL	V	61/2J	195	7.7	582	22.9	500	1102	290	42	340	49
205/45R16	8.0	10.0	87/XL	V	7J	206	8.1	590	23.2	545	1201	290	42	340	49
* 205/45R17	8.0	10.0	84	V	7J	206	8.1	616	24.3	500	1102	250	36	300	44
205/45RF17	8.0	10.0	84	V	7J	206	8.1	616	24.3	500	1102	250	36	300	44
	8.0	10.0	88/XL	V	7J	206	8.1	616	24.3	560	1235	290	42	340	49
205/45ZR16	8.0	10.0	87/XL	W	7J	206	8.1	590	23.2	545	1201	290	42	340	49
205/45ZR17	8.0	10.0	88/XL	W	7J	206	8.1	616	24.3	560	1235	290	42	340	49
215/45ZR17	8.0	10.0	87	W	7J	213	8.4	626	24.6	545	1201	250	36	300	44
215/45ZR17	8.0	10.0	91/XL	W	7J	213	8.4	626	24.6	615	1356	290	42	340	49
215/45ZRF17	8.0	10.0	87	W	7J	213	8.4	626	24.6	545	1201	250	36	300	44
225/45ZR17	8.0	10.0	91	W	71/2J	225	8.9	634	25.0	615	1356	250	36	300	44
	8.0	10.0	94/XL	W	71/2J	225	8.9	634	25.0	670	1477	290	42	340	49
235/45ZR17	8.0	10.0	94	W	8J	236	9.3	644	25.4	670	1477	250	36	300	44
	8.0	10.0	97/XL	W	8J	236	9.3	644	25.4	730	1609	290	42	340	49
	8.0	10.0	80	W	71/2J	212	8.3	596	23.5	450	992	250	36	300	44
205/40ZR17	8.0	10.0	84/XL	W	71/2J	212	8.3	596	23.5	500	1102	290	42	340	49
	8.0	10.0	86/XL	W	71/2J	218	8.6	578	22.8	530	1168	290	42	340	49
215/40ZR17	8.0	10.0	83	W	71/2J	218	8.6	604	23.8	487	1074	250	36	300	44
225/40ZR17	8.0	10.0	87/XL	W	71/2J	218	8.6	604	23.8	545	1201	290	42	340	49
	8.0	10.0	88	W	8J	230	9.1	637	25.1	560	1235	250	36	300	44
225/40ZR18	8.0	10.0	92/XL	W	8J	230	9.1	637	25.1	630	1389	290	42	340	49
	* 8.0	10.0	93/XL	W	8J	230	9.1	663	26.1	650	1433	290	42	340	49
235/40ZR17	8.0	10.0	90	W	81/2J	241	9.5	620	24.4	600	1323	250	36	300	44
	8.0	10.0	94/XL	W	81/2J	241	9.5	620	24.4	670	1477	290	42	340	49
235/40ZR18	8.0	10.0	91	W	81/2J	241	9.5	645	25.4	615	1356	250	36	300	44
	8.0	10.0	95/XL	W	81/2J	241	9.5	645	25.4	690	1521	290	42	340	49
* 245/40ZR19	8.0	10.0	94	W	81/2J	248	9.8	679	26.7	670	1477	250	36	300	44
	8.0	10.0	85/XL	W	71/2J	218	8.6	633	24.9	515	1135	290	42	340	49
225/35ZR19	8.0	10.0	88/XL	W	8J	230	9.1	641	25.2	560	1235	290	42	340	49
245/35ZR19	8.0	10.0	93/XL	W	81/2J	248	9.8	655	25.8	650	1433	290	42	340	49
* 245/35ZR20	8.0	10.0	95/XL	Y	81/2J	248	9.8	680	26.8	690	1521	290	42	340	49
* 245/30ZR20	8.0	10.0	97/XL	Y	81/2J	248	9.8	656	25.8	730	1609	290	42	340	49
	8.0	10.0	95/XL	Y	81/2J	248	9.8	656	25.8	690	1521	290	42	340	49
	8.0	10.0	90/XL	W	81/2J	248	9.8	656	25.8	600	1323	290	42	340	49

★ 2009 NEW PRODUCT

- Optimum tread design for comfort and performance.
- Asymmetrical tread pattern offer superb cornering stability and precision steering response.
- Four wide circumferential straight grooves for improved hydroplaning.
- Different tread patterns featured on either side optimize both wet and dry handling.



40/45/50/55/60/65 SERIES
T/H/V, M+S

SNOW TIRE

S-1083



45/50/55/60/65/70/80 SERIE
T/H/V, M+S

SNOW TIRE

S-1086



Tire Size	Tread Depth		Load Index	Speed symbol	Std.Rim	Section Width		Overall Diameter		Load Capacity		Std.Cold Infl.press		Max.permiss.press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
195/65R15	8.3	10.5	91	T	6J	201	7.9	635	25.0	615	1356	250	36	300	44
	8.3	10.5	95/XL	T	6J	201	7.9	635	25.0	690	1521	290	42	340	49
215/65R15	8.3	10.5	91	H	6J	201	7.9	635	25.0	615	1356	250	36	300	44
	8.3	10.5	96	H	61/2J	221	8.7	661	26.0	710	1565	250	36	300	44
215/65R16	8.3	10.5	98	H	61/2J	221	8.7	686	27.0	750	1653	250	36	300	44
205/60R16	8.3	10.5	96/XL	H	6J	209	8.2	652	25.7	710	1565	290	42	340	49
215/60R16	8.3	10.5	99/XL	H	61/2J	221	8.7	664	26.1	775	1709	290	42	340	49
* 185/55R15	8.3	10.5	86/XL	H	6J	194	7.6	585	23.0	530	1168	290	42	340	49
* 195/55R15	8.3	10.5	85	H	6J	201	7.9	595	23.4	515	1135	250	36	300	44
* 195/55R16	8.3	10.5	87	H	6J	201	7.9	620	24.4	545	1201	250	36	300	44
205/55R16	8.3	10.5	91	T	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
	8.3	10.5	91	H	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
* 215/55R16	8.3	10.5	97/XL	H	7J	226	8.9	642	25.3	730	1609	290	42	340	49
225/55R16	8.3	10.5	99/XL	H	7J	233	9.2	654	25.7	775	1709	290	42	340	49
* 195/50R15	8.3	10.5	82	H	6J	201	7.9	577	22.7	475	1047	250	36	300	44
* 205/50R17	8.3	10.5	93/XL	V	61/2J	214	8.4	638	25.1	650	1433	290	42	340	49
* 225/45R17	8.3	10.5	94/XL	V	71/2J	225	8.9	634	25.0	670	1477	290	42	340	49
205/40R17	8.3	10.5	84/XL	V	71/2J	212	8.3	596	23.5	500	1102	290	42	340	49

★ 2009 NEW PRODUCT

- Unidirectional tread design.
- Advanced tread compound for improved braking.
- Intricate sipe design ensures excellent braking and traction properties on ice and snow.
- Superior water drainage and snow removal.

Tire Size	Tread Depth		Load Index	Speed symbol	Std.Rim	Section Width		Overall Diameter		Load Capacity		Std.Cold Infl.press		Max.permiss.press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
155/80R13	9.6	12.0	79	T	41/2J	157	6.2	578	22.8	437	963	240	35	300	44
155/70R13	9.6	12.0	75	T	41/2J	157	6.2	548	21.6	387	853	250	36	300	44
165/70R13	9.6	12.0	79	T	5J	170	6.7	562	22.1	437	963	250	36	300	44
	9.6	12.0	83/XL	T	5J	170	6.7	562	22.1	487	1074	290	42	340	49
165/70R14	9.6	12.0	81	T	5J	170	6.7	588	23.1	462	1019	250	36	300	44
	9.6	12.0	85/XL	T	5J	170	6.7	588	23.1	515	1135	290	42	340	49
175/70R13	9.6	12.0	82	T	5J	177	7.0	576	22.7	475	1047	250	36	300	44
	9.6	12.0	84	T	5J	177	7.0	602	23.7	500	1102	250	36	300	44
175/70R14	9.6	12.0	88/XL	T	5J	177	7.0	602	23.7	560	1235	290	42	340	49
	9.6	12.0	88	T	51/2J	189	7.4	616	24.3	560	1235	250	36	300	44
185/70R14	9.6	12.0	86/XL	T	5J	177	7.0	584	23.0	530	1168	290	42	340	49
	9.6	12.0	82	T	5J	177	7.0	584	23.0	475	1047	250	36	300	44
185/65R14	9.6	12.0	86	T	51/2J	189	7.4	596	23.5	530	1168	250	36	300	44
	9.6	12.0	88	T	51/2J	189	7.4	621	24.4	560	1235	250	36	300	44
195/65R15	9.6	12.0	91	T	6J	201	7.9	635	25.0	615	1356	250	36	300	44
	9.6	12.0	95/XL	T	6J	201	7.9	635	25.0	690	1521	290	42	340	49
205/65R15	9.6	12.0	91	H	6J	201	7.9	635	25.0	615	1356	250	36	300	44
	9.6	12.0	94	T	6J	209	8.2	647	25.5	670	1477	250	36	300	44
185/60R14	9.6	12.0	99/XL	T	6J	209	8.2	647	25.5	775	1709	290	42	340	49
	9.6	12.0	86/XL	T	51/2J	189	7.4	578	22.8	530	1168	290	42	340	49
195/60R15	9.6	12.0	88	T	6J	201	7.9	615	24.2	560	1235	250	36	300	44
	9.2	11.5	91	T	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
205/55R16	9.2	11.5	94/XL	T	61/2J	214	8.4	632	24.9	670	1477	290	42	340	49
	9.2	11.5	91	H	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
215/55R16	9.6	12.0	97/XL	T	7J	226	8.9	642	25.3	730	1609	290	42	340	49
	9.6	12.0	97/XL	H	7J	226	8.9	642	25.3	730	1609	290	42	340	49
195/50R15	9.6	12.0	82	H	6J	201	7.9	577	22.7	475	1047	250	36	300	44
	9.6	12.0	94/XL	V	71/2J	225	8.9	634	25.0	670	1477	290	42	340	49

- Unidirectional tread design.
- The arrow type main center rib and sipes enhance steering response on snow road.
- Deeper and wider lateral grooves ensure tire grip and traction on snow, also channel away effectively in slushy condition.
- New full silica advanced compound provide maximal wet traction with reduced rolling resistance.



30/35/40/45/50/55/60 SERIES
H/V/W/Y
UTQG-280/A/A (EXCEPT UTQG FOR
235/60R16 IS-420/A/A)

UHP

S-1088



25/30/35/40/45 SERIES
V/W, M+S
UTQG-420/A/A

CROSSOVER AND SUV

S-1089

Tire Size	Tread Depth		Load Index	Speed symbol	Std. Rim	Section Width		Overall Diameter		Load Capacity		Std Cold Infl. press		Max. perm. press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
235/60ZR16	8.6	11.0	100	W	7J	240	9.4	688	27.1	800	1764	250	36	300	44
205/55R16	8.2	10.5	91	H	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
	8.2	10.5	91	V	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
205/55ZR16	8.2	10.5	91	W	61/2J	214	8.4	632	24.9	615	1356	250	36	300	44
215/55R16	8.0	10.0	93	V	7J	226	8.9	642	25.3	650	1433	250	36	300	44
215/55ZR16	8.0	10.0	93	W	7J	226	8.9	642	25.3	650	1433	250	36	300	44
	8.0	10.0	97/XL	W	7J	226	8.9	642	25.3	730	1609	290	42	340	49
225/55R16	8.0	10.0	99/XL	V	7J	233	9.2	654	25.7	775	1709	290	42	340	49
225/55ZR16	8.0	10.0	95	W	7J	233	9.2	654	25.7	690	1521	250	36	300	44
195/50R15	8.0	10.0	82	V	6J	201	7.9	577	22.7	475	1047	250	36	300	44
205/50R16	8.0	10.0	87	V	61/2J	214	8.4	612	24.1	545	1201	250	36	300	44
205/50ZR16	8.0	10.0	87	W	61/2J	214	8.4	612	24.1	545	1201	250	36	300	44
205/50ZR17	8.0	10.0	93/XL	W	61/2J	214	8.4	638	25.1	650	1433	290	42	340	49
235/50ZR18	8.0	10.0	97	W	71/2J	245	9.6	693	27.3	730	1609	250	36	300	44
195/45R15	8.0	10.0	78	V	61/2J	195	7.7	557	21.9	425	937	250	36	300	44
205/45R16	8.0	10.0	87/XL	V	7J	206	8.1	590	23.2	545	1201	290	42	340	49
205/45ZR16	8.0	10.0	87/XL	W	7J	206	8.1	590	23.2	545	1201	290	42	340	49
215/45ZR17	8.0	10.0	87	W	7J	213	8.4	626	24.6	545	1201	250	36	300	44
	8.0	10.0	91/XL	W	7J	213	8.4	626	24.6	615	1356	290	42	340	49
225/45ZR17	8.0	10.0	91	W	71/2J	225	8.9	634	25.0	615	1356	250	36	300	44
	8.0	10.0	94/XL	W	71/2J	225	8.9	634	25.0	670	1477	290	42	340	49
235/45ZR17	8.0	10.0	94	W	8J	236	9.3	644	25.4	670	1477	250	36	300	44
	8.0	10.0	97/XL	W	8J	236	9.3	644	25.4	730	1609	290	42	340	49
245/45ZR17	8.0	10.0	95	W	8J	243	9.6	652	25.7	690	1521	250	36	300	44
255/45ZR18	8.0	10.0	103/XL	W	81/2J	255	10.0	687	27.0	875	1929	290	42	340	49
	8.0	10.0	101	W	81/2J	255	10.0	738	29.1	825	1819	250	36	300	44
255/45ZR20	8.0	10.0	105/XL	W	81/2J	255	10.0	738	29.1	925	2039	290	42	340	49
	8.0	10.0	80	W	71/2J	212	8.3	596	23.5	450	992	250	36	300	44
205/40ZR17	8.0	10.0	84/XL	W	71/2J	212	8.3	596	23.5	500	1102	290	42	340	49
	8.0	10.0	86/XL	W	71/2J	218	8.6	578	22.8	530	1168	290	42	340	49
215/40ZR17	8.0	10.0	83	W	71/2J	218	8.6	604	23.8	487	1074	250	36	300	44
	8.0	10.0	87/XL	W	71/2J	218	8.6	604	23.8	545	1201	290	42	340	49
225/40ZR18	8.0	10.0	88	W	8J	230	9.1	637	25.1	560	1235	250	36	300	44
	8.0	10.0	92/XL	W	8J	230	9.1	637	25.1	630	1389	290	42	340	49
235/40ZR18	8.0	10.0	91	W	81/2J	241	9.5	645	25.4	615	1356	250	36	300	44
	8.0	10.0	95/XL	W	81/2J	241	9.5	645	25.4	690	1521	290	42	340	49
245/40ZR18	8.0	10.0	97/XL	W	81/2J	248	9.8	653	25.7	730	1609	290	42	340	49
275/40ZR20	8.0	10.0	106/XL	W	91/2J	278	10.9	728	28.7	950	2094	290	42	340	49
215/35ZR18	8.0	10.0	84/XL	W	71/2J	218	8.6	607	23.9	500	1102	290	42	340	49
225/35ZR20	8.0	10.0	90/XL	W	8J	230	9.1	666	26.2	600	1323	290	42	340	49
235/35ZR19	8.0	10.0	91/XL	W	81/2J	241	9.5	647	25.5	615	1356	290	42	340	49
245/35ZR19	8.0	10.0	93/XL	W	81/2J	248	9.8	655	25.8	650	1433	290	42	340	49
245/35ZR20	8.0	10.0	95/XL	W	81/2J	248	9.8	680	26.8	690	1521	290	42	340	49
255/35ZR18	8.0	10.0	94/XL	W	9J	260	10.2	635	25.0	670	1477	290	42	340	49
255/35ZR20	8.0	10.0	97/XL	Y	9J	260	10.2	686	27.0	730	1609	290	42	340	49
265/35ZR18	8.0	10.0	97/XL	W	91/2J	271	10.7	643	25.3	730	1609	290	42	340	49
225/30ZR20	8.0	10.0	85/XL	W	8J	230	9.1	644	25.4	515	1135	290	42	340	49
255/30ZR22	8.0	10.0	95/XL	W	9J	260	10.2	713	28.1	690	1521	290	42	340	49

Tire Size	Tread Depth		Load Index	Speed symbol	Std. Rim	Section Width		Overall Diameter		Load Capacity		Std Cold Infl. press		Max. perm. press	
	mm	32nds				mm	inch	mm	inch	kg	lbs	kPa	psi	kPa	psi
245/40ZR20	8.0	10.0	99/XL	W	81/2J	248	9.8	704	27.7	775	1709	290	42	340	49
255/40ZR20	8.0	10.0	101/XL	W	9J	260	10.2	712	28.0	825	1819	290	42	340	49
245/35ZR20	8.0	10.0	95/XL	W	81/2J	248	9.8	680	26.8	690	1521	290	42	340	49
255/35ZR19	8.0	10.0	96/XL	W	9J	260	10.2	661	26.0	710	1565	290	42	340	49
255/35ZR20	8.0	10.0	97/XL	W	9J	260	10.2	686	27.0	730	1609	290	42	340	49
275/35ZR20	8.0	10.0	102/XL	W	91/2J	278	10.9	700	27.6	850	1874	290	42	340	49
325/35R28	8.9	11.0	120/XL	V	111/2J	331	13.0	939	37.0	1400	3086	290	42	340	49
235/30ZR22	8.0	10.0	90/XL	W	81/2J	242	9.5	701	27.6	600	1323	290	42	340	49
245/30ZR22	8.0	10.0	92/XL	W	81/2J	248	9.8	707	27.8	630	1389	290	42	340	49
255/30ZR24	8.0	10.0	97/XL	W	9J	260	10.2	764	30.1	730	1609	290	42	340	49
★ 265/30ZR19	8.0	10.0	93/XL	W	91/2J	271	10.7	643	25.3	650	1433	290	42	340	49
	8.0	10.0	89	W	91/2J	271	10.7	643	25.3	580	1279	250	36	300	44
265/30ZR22	8.0	10.0	97/XL	W	91/2J	271	10.7	719	28.3	730	1609	290	42	340	49
275/30ZR19	8.0	10.0	96/XL	W	91/2J	278	10.9	649	25.6	710	1565	290	42	340	49
★ 275/30ZR20	8.0	10.0	97/XL	W	91/2J	278	10.9	674	26.5	730	1609	290	42	340	49
	8.8	11.0	101/XL	W	91/2J	278	10.9	776	30.6	825	1819	290	42	340	49
285/30ZR20	8.8	11.0	99/XL	W	10J	290	11.4	680	26.8	775	1709	290	42	340	49
295/30ZR26	8.8	11.0	107/XL	W	101/2J	301	11.9	838	33.0	975	2149	290	42	340	49
305/30ZR26	8.8	11.0	109/XL	W	11J	313	12.3	844	33.2	1030	2271	290	42	340	49
275/25ZR24	8.8	11.0	95/XL	W	10J	283	11.1	747	29.4	690	1521	290	42	340	49
★ 285/25ZR20	8.0	10.0	93/XL	W	101/2J	295	11.6	650	25.6	650	1433	290	42	340	49
	8.0	10.0	97/XL	W	101/2J	301	11.9	707	27.8	730	1609	290	42	340	49

★ 2009 NEW PRODUCT

- Outstanding tread design for A/S UHP.
- Noise-minimizing tread block pattern.
- Wide, circumferential grooves that channel water away.
- Double V grooves provide super traction and grip.

- Slip resistant tire pattern designed with unidirectional “人” type enables high speed, prompt water evacuation and ensures safety in the event of slip.
- Endurable, stable and comfortable and low noise, high speed up to 300km/h.
- Unique design of biological modeling pattern, streamlined and stylish.
- Suitable for BMW, Audi and etc.